Akira TAKAYASU et al. Serial No. 10/567,684 Attorney Docket No. 2006_0076A April 11, 2008

AMENDMENTS TO THE CLAIMS

- 1. (Currently amended) A sound-absorbing material, wherein (a) a non-woven fabric with a mass per unit area of 150 to 800 g/m² and a bulk density of 0.01 to 0.2 g/cm³ and (b) a surface material with an air permeability of not more than 50 cc/cm²/sec measured according to JIS L-1096 are layered, and wherein the surface material (b) is a spun bonded non-woven fabric or a wet-laid non-woven staple fabric.
- 2. (Currently amended) The sound-absorbing material according to claim 1, wherein the non-woven fabric (a) is a fabric in which a thermoplastic staple fiber and a heat resistant staple fiber with an LOI value of not less than 25 are intertwisted.
- 3. (Original) The sound-absorbing material according to claim 2, wherein the weight ratio of the thermoplastic staple fiber and the heat resistant staple fiber is in a range of 95:5 to 55:45.
- 4. (Original) The sound-absorbing material according to claim 2, wherein the weight ratio of the thermoplastic staple fiber and the heat resistant staple fiber is in a range of 85:15 to 55:45.
- 5. (Currently amended) The sound-absorbing material according to claim 2, wherein the thermoplastic staple fiber is at least one kind of staple fibers fiber selected from the group consisting of a polyester fiber, a polypropylene fiber and a nylon fiber.
- 6. (Currently amended) The sound-absorbing material according to claim 2, wherein the heat resistant staple fiber is at least one kind of staple-fibers fiber selected from the group consisting of an aramid fiber, a polyphenylene sulfide fiber, a polybenzoxazole fiber, a polybenzothiazole fiber, a polybenzimidazole fiber, a polyether ether ketone fiber, a polyarylate fiber, a polyimide fiber, a fluoride fiber and a flame resistant fiber.

Akira TAKAYASU et al. Serial No. 10/567,684 Attorney Docket No. 2006_0076A April 11, 2008

- 7. (Previously presented) The sound-absorbing material according to claim 2, wherein the thermoplastic staple fiber is a polyester staple fiber and the heat resistant staple fiber is an aramid staple fiber.
- 8. (Currently amended) The sound-absorbing material according to claim 1, wherein the non-woven fabric (a) is produced by needle punch method or water jet method.

9. (Cancelled)

- 10. (Currently amended) The sound-absorbing material according to elaim 9 claim 1, wherein the wet-laid non-woven fabric is comprised of a heat resistant staple fiber with an LOI value of not less than 25.
- 11. (Currently amended) The sound-absorbing material according to claim 9 claim 1, wherein the wet-laid non-woven fabric is comprised of a heat resistant staple fiber with an LOI value of not less than 25 and a silicate mineral.
- 12. (Original) The sound-absorbing material according to claim 11, wherein the silicate mineral is mica.
- 13. (Previously presented) The sound-absorbing material according to claim 10, wherein the heat resistant staple fiber is an aramid staple fiber.
- 14. (Currently amended) The sound-absorbing material according to claim 9 claim 1, wherein the surface material (b) has a dust generation number of not more than 500 particles/0.1 ft³ of particles with a diameter of not less than 0.3 μm measured by the tumbling method according to JIS B-9923 6.2(1.2).

Akira TAKAYASU et al. Serial No. 10/567,684 Attorney Docket No. 2006_0076A

April 11, 2008

15. (Currently amended) The sound-absorbing material according to claim 1, wherein the

non-woven fabric (a) and the surface material (b) are comprised of the same kind of synthetic

fiber.

16. (Currently amended) The sound-absorbing material according to claim 1, wherein the

non-woven fabric (a) and the surface material (b) are layered by bonding, and the number of the

bonding points of the non-woven fabric and the surface material is not more than 30 points/cm²,

and the ratio of the total surface area of the bonding points to the total surface area of the

bonding points and the non-bonding points is not more than 30%.

17. (Currently amended) The sound-absorbing material according to claim 1, wherein the

non-woven fabric (a) is in the shape of a polyhedron and the surface material (b) is layered on

two or more faces of the polyhedron.

18. (Currently amended) The sound-absorbing material according to claim 17, wherein the

non-woven fabric (a) is in the shape of a hexahedron and the surface material (b) is layered on

both side faces of the hexahedron.

19. (Currently amended) The sound-absorbing material according to claim 1, wherein the

non-woven fabric (a) is in the shape of a column or a cylinder and the surface material (b) is

layered on the curved face of the column or the cylinder.

20. (Currently amended) The sound-absorbing material according to claim 1 having a

multilayer structure comprising at least one or more layers of each of the non-woven fabric (a)

and the surface-layer material (b), wherein the both layers are united.

21. (Previously presented) The sound-absorbing material according to claim 1, which is

used as a vehicle interior material or a vehicle exterior material.

5

Akira TAKAYASU et al. Serial No. 10/567,684 Attorney Docket No. 2006_0076A April 11, 2008

- 22. (Previously presented) The sound-absorbing material according to claim 1, which is used as a sound-absorbing material for a lawn mower.
- 23. (Previously presented) The sound-absorbing material according to claim 1, which is used as a sound-absorbing material for a breaker.